

Description

cadmium plated steel, slotted recess, total panel thickness: 0.210 - 0.239

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|----------------------------------------|
| SKU / Model: | 11270007 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5325-01-242-6074 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



* See page 2 for technical characteristics

P/N 1127000-7 Specifications

| | |
|-------------------------------------------------------------------|-----------------------------------------------|
| Diameter: | 0.251 Inches Minimum And 0.256 Inches Maximum |
| Turnlock Stud Head Style: | Stud Head |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.641 Inches Minimum And 0.651 Inches Maximum |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.328 Inches Nominal |
| Material Accommodated Thickness: | 0.180 Inches Minimum And 0.239 Inches Maximum |
| Drive Type: | Slotted |
| Stud Head Height: | 0.069 Inches Minimum And 0.076 Inches Maximum |
| Material: | Steel Ejector Spring |
| Material: | Steel Eyelet |
| Material: | Steel Pin |
| Material: | Steel Stud |
| Surface Treatment: | Cadmium Overall And Chromate Overall |

How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1127000-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.