

**Description**

cadmium plated steel slotted recess - total panel thickness 0.240" - 0.269"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	11270008
Minimum Qty (MOQ):	10
NSN:	5325-00-171-4237



\* See page 2 for technical characteristics

# P/N 1127000-8 Specifications

Diameter:	0.253 Inches Nominal
Securing Device Type:	Washer
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.671 Inches Minimum And 0.681 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.328 Inches Nominal
Material Accommodated Thickness:	0.240 Inches Minimum And 0.269 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.072 Inches Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1127000-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.