

Description

corrosion resistant steel - slotted recess - total panel thickness 0.150" - 0.179

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[2700-5S](#)

| | |
|-------------------------|--|
| SKU / Model: | 11270035 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5325-00-849-8512 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



* See page 2 for technical characteristics

P/N 1127003-5 Specifications

| | |
|--|--|
| Diameter: | 0.251 Inches Minimum And 0.256 Inches Maximum |
| Turnlock Stud Head Style: | Stud Head |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.581 Inches Minimum And 0.591 Inches Maximum |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.328 Inches Nominal |
| Material Accommodated Thickness: | 0.120 Inches Minimum And 0.179 Inches Maximum |
| Drive Type: | Slotted |
| Stud Head Height: | 0.069 Inches Minimum And 0.076 Inches Maximum |
| Material: | Steel Comp 302 Ejector Spring |
| Material: | Steel Comp 302 Stud |
| Material: | Steel Comp 302 Pin |
| Material: | Steel Comp 305 Eyelet |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1127003-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.