

P/N 1127003-8

Military-Fasteners.com

### Description

corrosion resistant steel, slotted recess, total panel thickness 0.240" - 0.269

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

<u>2700-85</u>	
SKU / Model:	11270038
Minimum Qty (MOQ):	5
NSN:	5325-00-601-7303
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



# P/N 1127003-8 Specifications

Diameter:	0.251 Inches Minimum And 0.256 Inches Maximum
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.674 Inches Minimum And 0.681 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.328 Inches Nominal
Material Accommodated Thickness:	0.210 Inches Minimum And 0.269 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.069 Inches Minimum And 0.076 Inches Maximum
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 302 Stud
Material:	Steel Comp 302 Pin
Material:	Steel Comp 305 Eyelet
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

## **How to Order**

Order this turnlock fastener stud assembly from our inventory online by visiting <u>https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1127003-8</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.