

Description

cadmium plated steel philips recess, total panel thickness 0.390" - 0.419

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[27S3-13](#)

| | |
|--------------------|------------------|
| SKU / Model: | 112700413 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5325-01-175-5742 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N 1127004-13 Specifications

| | |
|--|---|
| Diameter: | 0.251 Inches Minimum And 0.256 Inches Maximum |
| Turnlock Stud Head Style: | Stud Head |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.831 Inches Nominal |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.328 Inches Nominal |
| Material Accommodated Thickness: | 0.390 Inches Minimum And 0.419 Inches Maximum |
| Drive Type: | Cross Recess |
| Stud Head Height: | 0.073 Inches Nominal |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1127004-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.