

Description

cadmium plated steel philips recess, total panel thickness 0.390" - 0.419

* Manufacturer certifications are shipped with your order FREE of charge


Order this part online

Additional Information

Alternate Part Numbers

[27S3-13](#)

SKU / Model:	112700413
Minimum Qty (MOQ):	1
NSN:	5325-01-175-5742
ECCN:	EAR99



* See page 2 for technical characteristics

P/N 1127004-13 Specifications

Diameter:	0.251 Inches Minimum And 0.256 Inches Maximum
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.831 Inches Nominal
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.328 Inches Nominal
Material Accommodated Thickness:	0.390 Inches Minimum And 0.419 Inches Maximum
Drive Type:	Cross Recess
Stud Head Height:	0.073 Inches Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1127004-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.