

Description

cadmium plated steel philips recess - total panel thickness 0.420" - 0.449"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | 112700414 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5325-01-013-1489 |



P/N 1127004-14 Specifications

| | |
|--------------------------------------------------------------------------|-----------------------------------------------|
| Diameter: | 0.244 Inches Minimum And 0.256 Inches Maximum |
| Securing Device Type: | Washer |
| Turnlock Stud Head Style: | Stud Head |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 1.000 Inches Nominal |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.328 Inches Nominal |
| Material Accommodated Thickness: | 0.780 Inches Minimum And 0.809 Inches Maximum |
| Drive Type: | Cross Recess |
| Stud Head Height: | 0.073 Inches Nominal |
| Material: | Steel Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1127004-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.