

**Description**

total panel thickness 0.090" - 0.119", cadmium plated steel philips recess

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

27S3-3

SKU / Model:	11270043
Minimum Qty (MOQ):	5
NSN:	5325-00-701-9695
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

# P/N 1127004-3 Specifications

Diameter:	0.244 Inches Minimum And 0.256 Inches Maximum
Securing Device Type:	Ring
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.521 Inches Minimum And 0.531 Inches Maximum
Eyelet Outside Diameter:	0.244 Inches Minimum And 0.250 Inches Maximum
Eyelet Length:	0.328 Inches Nominal
Material Accommodated Thickness:	0.090 Inches Minimum And 0.119 Inches Maximum
Drive Type:	Cross Recess
Stud Head Height:	0.069 Inches Minimum And 0.076 Inches Maximum
Material:	Steel Comp 1212 Eyelet
Material:	Steel Comp 4037 Stud
Material:	Steel Ejector Spring
Material:	Steel Pin
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting<https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1127004-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out[here](#) to complete your order.