

Description

total panel thickness 0.090" - 0.119", cadmium plated steel philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[27S3-3](#)

| | |
|-------------------------|----------------------------------------|
| SKU / Model: | 11270043 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5325-00-701-9695 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



* See page 2 for technical characteristics

P/N 1127004-3 Specifications

| | |
|--------------------------------------------------------------------------|---------------------------------------------------------------|
| Diameter: | 0.244 Inches Minimum And 0.256 Inches Maximum |
| Securing Device Type: | Ring |
| Turnlock Stud Head Style: | Stud Head |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.521 Inches Minimum And 0.531 Inches Maximum |
| Eyelet Outside Diameter: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Eyelet Length: | 0.328 Inches Nominal |
| Material Accommodated Thickness: | 0.090 Inches Minimum And 0.119 Inches Maximum |
| Drive Type: | Cross Recess |
| Stud Head Height: | 0.069 Inches Minimum And 0.076 Inches Maximum |
| Material: | Steel Comp 1212 Eyelet |
| Material: | Steel Comp 4037 Stud |
| Material: | Steel Ejector Spring |
| Material: | Steel Pin |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1127004-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.