

Description

slotted - fillister head - stud assembly - dia: 1/2", steel - cadmium and chromate plated - total panel thickness 0.090" - 0.119

* Manufacturer certifications are shipped with your order FREE of charge


Order this part online

Additional Information

Alternate Part Numbers

[28S14-3](#)

SKU / Model:	11280003
Minimum Qty (MOQ):	2
NSN:	5325-01-150-4867
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 1128000-3 Specifications

Diameter:	0.489 Inches Minimum And 0.511 Inches Maximum
Securing Device Type:	Washer
Turnlock Stud Head Style:	Fillister
Stud Assembly Style:	Stud Assembly
Eyelet Outside Diameter:	0.519 Inches Minimum And 0.531 Inches Maximum
Stud Diameter:	0.305 Inches Minimum And 0.315 Inches Maximum
Material Accommodated Thickness:	0.090 Inches Minimum And 0.119 Inches Maximum
Drive Type:	Slotted
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1128000-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.