

Description

cadmium plated steel slotted recess - total panel thickness 0.051" - 0.080"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	11420002
Minimum Qty (MOQ):	10
NSN:	5325-00-639-4899



P/N 1142000-2 Specifications

Diameter:	0.380 Inches Nominal
Turnlock Stud Head Style:	Flat Countersunk
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.453 Inches Minimum And 0.463 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.220 Inches Nominal
Material Accommodated Thickness:	0.081 Inches Minimum And 0.110 Inches Maximum
Drive Type:	Slotted
Material:	Steel Ejector Spring
Material:	Steel Eyelet
Material:	Steel Pin
Material:	Steel Stud
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142000-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.