

**Description**

cadmium plated steel slotted recess - total panel thickness 0.051" - 0.080"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	11420002
Minimum Qty (MOQ):	10
NSN:	5325-00-639-4899

NO IMAGE  
AVAILABLE

## P/N 1142000-2 Specifications

<b>Diameter:</b>	0.380 Inches Nominal
<b>Turnlock Stud Head Style:</b>	Flat Countersunk
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.453 Inches Minimum And 0.463 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.341 Inches Minimum And 0.348 Inches Maximum
<b>Eyelet Length:</b>	0.220 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.081 Inches Minimum And 0.110 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Material:</b>	Steel Ejector Spring
<b>Material:</b>	Steel Eyelet
<b>Material:</b>	Steel Pin
<b>Material:</b>	Steel Stud
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142000-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.