

## P/N 1142000-24

### **Description**

Diameter: 3/8", steel ejector spring

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: 114200024

Minimum Qty (MOQ): 5 EA

NSN: 5325-00-449-3019

Schedule B: 7318.15.5030

ECCN: EAR99

National Motor Freight: 066440, Fasteners Curtain / Snap Metal



<sup>\*</sup> See page 2 for technical characteristics

# P/N 1142000-24 Specifications

Diameter:	0.377 Inches Minimum And 0.384 Inches Maximum
Turnlock Stud Head Style:	Flat Countersunk
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	1.113 Inches Minimum And 1.123 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.257 Inches Nominal
Material Accommodated Thickness:	0.741 Inches Minimum And 0.770 Inches Maximum
Drive Type:	Slotted
Material:	Steel Comp 1009 Eyelet Or Steel Comp 1050 Eyelet Or Steel Comp 1112 Eyelet
Material:	Steel Comp 4037 Stud
Material:	Steel Ejector Spring
Material:	Steel Pin
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Ejector Spring
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Pin
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall

## **How to Order**

Order this 1/4 turn stud from our inventory online by visiting <a href="https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142000-24">https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142000-24</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.