

Description

Diameter: 3/8", steel overall

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | 114200026 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5325-00-297-9652 |
| Schedule B: | 7318.15.5030 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |

NO IMAGE
AVAILABLE

P/N 1142000-26 Specifications

| | |
|--|---|
| Diameter: | 0.377 Inches Minimum And 0.384 Inches Maximum |
| Turnlock Stud Head Style: | Flat Countersunk |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 1.173 Inches Minimum And 1.183 Inches Maximum |
| Eyelet Outside Diameter: | 0.341 Inches Minimum And 0.348 Inches Maximum |
| Eyelet Length: | 0.257 Inches Nominal |
| Material Accommodated Thickness: | 0.801 Inches Minimum And 0.830 Inches Maximum |
| Drive Type: | Slotted |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |

How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142000-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.