

Description

cadmium plated steel - slotted recess, total panel thickness: 0.141" - 0.170"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|----------------------------------------|
| SKU / Model: | 11420005 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5325-00-290-8235 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



* See page 2 for technical characteristics

P/N 1142000-5 Specifications

| | |
|--------------------------------------------------------------------------|-------------------------------------------------------------|
| Diameter: | 0.377 Inches Minimum And 0.384 Inches Maximum |
| Turnlock Stud Head Style: | Flat Countersunk |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.543 Inches Minimum And 0.583 Inches Maximum |
| Eyelet Outside Diameter: | 0.341 Inches Minimum And 0.348 Inches Maximum |
| Eyelet Length: | 0.292 Inches Nominal |
| Material Accommodated Thickness: | 0.171 Inches Minimum And 0.200 Inches Maximum |
| Drive Type: | Slotted |
| Material: | Steel Comp 4037 Stud |
| Material: | Steel Ejector Spring |
| Material: | Steel Eyelet |
| Material: | Steel Pin |
| Material Document And Classification: | Qq-w-470 Fed Spec Single Material Response Ejector Spring |
| Material Document And Classification: | Qq-w-470 Fed Spec Single Material Response Pin |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2 Cl 2 Fed Spec All Treatment Responses Overall |

How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142000-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.