

P/N 1142000-7

Description

cadmium plated steel slotted recess - total panel thickness 0.201" - 0.230"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	11420007
Minimum Qty (MOQ):	10
NSN:	5325-00-290-8233
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



^{*} See page 2 for technical characteristics

P/N 1142000-7 Specifications

Diameter:	0.377 Inches Minimum And 0.384 Inches Maximum
Securing Device Type:	Spring
Turnlock Stud Head Style:	Flat Countersunk
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.603 Inches Minimum And 0.613 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.352 Inches Nominal
Material Accommodated Thickness:	0.231 Inches Minimum And 0.260 Inches Maximum
Drive Type:	Slotted
Material:	Steel Overall
Material Document And Classification:	Astm A547 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Astm B633 Assn Std Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142000-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142000-7