



MILITARY ★ FASTENERS

Military-Fasteners.com

P/N 1142000-9

Description

total panel thickness 0.261" - 0.29", cadmium plated steel, slotted recess,

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	11420009
Minimum Qty (MOQ):	10
NSN:	5325-00-171-5789
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 1142000-9 Specifications

Diameter:	0.377 Inches Minimum And 0.384 Inches Maximum
Securing Device Type:	Spring
Turnlock Stud Head Style:	Flat Countersunk
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.663 Inches Minimum And 0.673 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.412 Inches Nominal
Material Accommodated Thickness:	0.291 Inches Minimum And 0.320 Inches Maximum
Drive Type:	Slotted
Material:	Steel Comp 1009 Eyelet Or Steel Comp 1050 Eyelet Or Steel Comp 1112 Eyelet
Material:	Steel Comp 4037 Stud
Material:	Steel Ejector Spring
Material:	Steel Pin
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Ejector Spring
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Pin
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-41,ty 2 Cl 2 Fed Spec All Treatment Responses Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142000-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.