

## Description

corrosion resistant steel, slotted recess, total panel thickness 0.291" - 0.320

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[4002-10S](#)

SKU / Model:	114200210
Minimum Qty (MOQ):	5
NSN:	5325-00-839-2277
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 1142002-10 Specifications

<b>Diameter:</b>	0.377 Inches Minimum And 0.384 Inches Maximum
<b>Turnlock Stud Head Style:</b>	Flat Countersunk
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.653 Inches Minimum And 0.703 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.341 Inches Minimum And 0.348 Inches Maximum
<b>Eyelet Length:</b>	0.442 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.321 Inches Minimum And 0.350 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Material:</b>	Steel Comp 302 Ejector Spring
<b>Material:</b>	Steel Comp 302 Stud
<b>Material:</b>	Steel Comp 302 Pin
<b>Material:</b>	Steel Comp 305 Eyelet
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142002-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.