

Description

corrosion resistant steel, slotted recess, total panel thickness 0.051" - 0.080

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[4002-2S](#)

SKU / Model:	11420022
Minimum Qty (MOQ):	5
NSN:	5325-00-514-9354
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



P/N 1142002-2 Specifications

Diameter:	0.377 Inches Minimum And 0.384 Inches Maximum
Securing Device Type:	Washer
Turnlock Stud Head Style:	Flat Countersunk
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.458 Inches Nominal
Eyelet Outside Diameter:	0.345 Inches Nominal
Eyelet Length:	0.220 Inches Nominal
Material Accommodated Thickness:	0.051 Inches Minimum And 0.110 Inches Maximum
Drive Type:	Slotted
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 302 Stud
Material:	Steel Comp 302 Pin
Material:	Steel Comp 305 Eyelet
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142002-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.