

Description

corrosion resistant steel, slotted recess, total panel thickness 0.081" - 0.110

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[4002-3S](#)

SKU / Model:	11420023
Minimum Qty (MOQ):	2
NSN:	5325-00-582-7769
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



P/N 1142002-3 Specifications

Diameter:	0.377 Inches Minimum And 0.384 Inches Maximum
Turnlock Stud Head Style:	Flat Countersunk
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.483 Inches Minimum And 0.493 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.257 Inches Nominal
Material Accommodated Thickness:	0.021 Inches Minimum And 0.140 Inches Maximum
Drive Type:	Slotted
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 302 Stud
Material:	Steel Comp 302 Pin
Material:	Steel Comp 305 Eyelet
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142002-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.