

Description

corrosion resistant steel, slotted recess, total panel thickness 0.111" - 0.140

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[4002-4S](#)

| | |
|-------------------------|--|
| SKU / Model: | 11420024 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5325-00-582-7773 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



P/N 1142002-4 Specifications

| | |
|--|--|
| Diameter: | 0.377 Inches Minimum And 0.384 Inches Maximum |
| Turnlock Stud Head Style: | Flat Countersunk |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.503 Inches Minimum And 0.513 Inches Maximum |
| Eyelet Outside Diameter: | 0.341 Inches Minimum And 0.348 Inches Maximum |
| Eyelet Length: | 0.257 Inches Nominal |
| Material Accommodated Thickness: | 0.021 Inches Minimum And 0.170 Inches Maximum |
| Drive Type: | Slotted |
| Material: | Steel Comp 302 Ejector Spring |
| Material: | Steel Comp 302 Stud |
| Material: | Steel Comp 302 Pin |
| Material: | Steel Comp 305 Eyelet |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142002-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.