

**Description**

corrosion resistant steel, slotted recess, total panel thickness 0.201" - 0.230

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[4002-7S](#)

SKU / Model:	11420027
Minimum Qty (MOQ):	5
NSN:	5325-00-810-8651
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



## P/N 1142002-7 Specifications

<b>Diameter:</b>	0.377 Inches Minimum And 0.384 Inches Maximum
<b>Turnlock Stud Head Style:</b>	Flat Countersunk
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.603 Inches Minimum And 0.613 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.341 Inches Minimum And 0.348 Inches Maximum
<b>Eyelet Length:</b>	0.352 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.201 Inches Minimum And 0.230 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Material:</b>	Steel Comp 302 Ejector Spring
<b>Material:</b>	Steel Comp 302 Stud
<b>Material:</b>	Steel Comp 302 Pin
<b>Material:</b>	Steel Comp 305 Eyelet
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142002-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.