

Description

corrosion resistant steel, slotted recess, total panel thickness 0.261" - 0.290

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[4002-9S](#)

SKU / Model:

11420029

Minimum Qty (MOQ):

5

NSN:

5325-00-057-4854

ECCN:

EAR99

National Motor Freight:

066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 1142002-9 Specifications

Diameter:	0.377 Inches Minimum And 0.384 Inches Maximum
Turnlock Stud Head Style:	Flat Countersunk
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.663 Inches Minimum And 0.673 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.412 Inches Nominal
Material Accommodated Thickness:	0.231 Inches Minimum And 0.260 Inches Maximum
Drive Type:	Slotted
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 302 Stud
Material:	Steel Comp 302 Pin
Material:	Steel Comp 305 Eyelet
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142002-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.