

Description

cadmium plated steel philips recess, total panel thickness 0.291" - 0.320

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[40S5-10](#)

SKU / Model:	114200510
Minimum Qty (MOQ):	5
NSN:	5325-01-124-1299
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 1142005-10 Specifications

Diameter:	0.377 Inches Minimum And 0.384 Inches Maximum
Securing Device Type:	Spring
Turnlock Stud Head Style:	Flat Countersunk
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.693 Inches Minimum And 0.703 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.432 Inches Minimum And 0.452 Inches Maximum
Material Accommodated Thickness:	0.321 Inches Minimum And 0.350 Inches Maximum
Drive Type:	Cross Recess
Material:	Steel Comp 1009 Eyelet Or Steel Comp 1050 Eyelet Or Steel Eyelet
Material:	Steel Comp 4037 Stud
Material:	Steel Ejector Spring
Material:	Steel Pin
Material Document And Classification:	Astm A108 Assn Std Single Material Response Eyelet
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Ejector Spring
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Pin
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142005-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.