

Description

cadmium plated steel philips recess, total panel thickness 0.441" - 0.470

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[40S5-15](#)

| | |
|-------------------------|--|
| SKU / Model: | 114200515 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5325-01-314-4973 |
| ECCN: | EAR99 |
| National Motor Freight: | 179735, Studs Vehicle Tire Roadway Surface |



P/N 1142005-15 Specifications

| | |
|---|---|
| Diameter: | 0.377 Inches Minimum And 0.384 Inches Maximum |
| Turnlock Stud Head Style: | Flat Countersunk |
| Stud Assembly Style: | Stud Assembly |
| Eyelet Outside Diameter: | 0.341 Inches Minimum And 0.348 Inches Maximum |
| Material Accommodated Thickness: | 0.471 Inches Minimum And 0.500 Inches Maximum |
| Drive Type: | Cross Recess |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142005-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.