

Description

cadmium plated steel philips recess, total panel thickness 0.471" - 0.500

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[40S5-16](#)

SKU / Model:	114200516
Minimum Qty (MOQ):	5
NSN:	5325-01-501-6711
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N 1142005-16 Specifications

Diameter:	0.377 Inches Minimum And 0.384 Inches Maximum
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.863 Inches Minimum And 0.883 Inches Maximum
Eyelet Outside Diameter:	0.412 Inches Minimum And 0.427 Inches Maximum
Eyelet Length:	0.237 Inches Minimum And 0.267 Inches Maximum
Drive Type:	Cross Recess
Stud Head Height:	0.092 Inches Minimum And 0.112 Inches Maximum
Part Name Assigned By Controlling Agency:	Stud Assembly, Panel Fastener 1/4turn
Special Features:	Joint Stars Aircraft
Material:	Steel Overall
Material Document And Classification:	Ams 6300 Assn Std Single Material Response Overall Or Astm A331 Assn Std Single Material Response Overall Or Astm A322 Assn Std Single Material Response Overall Or Astm A752 Assn Std Single Material Response Overall Or Astm A547 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142005-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.