

Description

cadmium plated steel philips recess, total panel thickness 0.471" - 0.500

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[40S5-16](#)

| | |
|--------------------|------------------|
| SKU / Model: | 114200516 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5325-01-501-6711 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N 1142005-16 Specifications

| | |
|--|--|
| Diameter: | 0.377 Inches Minimum And 0.384 Inches Maximum |
| Turnlock Stud Head Style: | Stud Head |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.863 Inches Minimum And 0.883 Inches Maximum |
| Eyelet Outside Diameter: | 0.412 Inches Minimum And 0.427 Inches Maximum |
| Eyelet Length: | 0.237 Inches Minimum And 0.267 Inches Maximum |
| Drive Type: | Cross Recess |
| Stud Head Height: | 0.092 Inches Minimum And 0.112 Inches Maximum |
| Part Name Assigned By Controlling Agency: | Stud Assembly, Panel Fastener 1/4turn |
| Special Features: | Joint Stars Aircraft |
| Material: | Steel Overall |
| Material Document And Classification: | Ams 6300 Assn Std Single Material Response Overall Or Astm A331 Assn Std Single Material Response Overall Or Astm A322 Assn Std Single Material Response Overall Or Astm A752 Assn Std Single Material Response Overall Or Astm A547 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142005-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.