

Description

cadmium plated steel philips recess, total panel thickness 0.081" - 0.110

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[40S5-3](#)

SKU / Model:	11420053
Minimum Qty (MOQ):	10
NSN:	5325-00-639-0561
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 1142005-3 Specifications

Diameter:	0.377 Inches Minimum And 0.384 Inches Maximum
Turnlock Stud Head Style:	Stud Head
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.403 Inches Minimum And 0.413 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.257 Inches Nominal
Material Accommodated Thickness:	0.111 Inches Minimum And 0.140 Inches Maximum
Drive Type:	Cross Recess
Stud Head Height:	0.102 Inches Nominal
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Ejector Spring
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Pin
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/1142005-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.