



Military-Fasteners.com

P/N 120-225-3R14

Description

Fastener Length: 1", Thread: 10-32, Thread Length: 27/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	1202253R14
Minimum Qty (MOQ):	50
NSN:	5305-01-524-1511
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N 120-225-3R14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.429 Inches Nominal
Fastener Length:	1.000 Inches Nominal
Head Style:	Round Extended Washer
Head Diameter:	0.375 Inches Nominal
Head Height:	0.094 Inches Nominal
Extended Washer Diameter:	0.437 Inches Nominal
Extended Washer Thickness:	0.027 Inches Nominal
Grip Diameter:	0.189 Inches Nominal
Internal Drive Style:	Cruciform Ribbed
End Item Identification:	Support Of Pre-provisioning Items For Which Navicp Phil Acts As Poe (e-nsn Isil)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.438 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	2000 Pounds Per Square Inch
Criticality Code Justification:	Agav
Part Name Assigned By Controlling Agency:	Screw, Washer Head, Close Tolerance, Long Thread, 95 Ksi Fsu
Material:	Steel Comp 4340 Overall
Material Document And Classification:	Ams6415 Assn Std 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type 2, Class2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/120-225-3R14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.