

## Description

Fastener Length: 1", Thread: 10-32, Thread Length: 27/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |                               |
|-------------------------|-------------------------------|
| SKU / Model:            | 1202253R14                    |
| Minimum Qty (MOQ):      | 50                            |
| NSN:                    | 5305-01-524-1511              |
| Schedule B:             | 7318.15.6080                  |
| ECCN:                   | EAR99                         |
| National Motor Freight: | 096640, Screws, Iron Or Steel |



## P/N 120-225-3R14 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.429 Inches Nominal  |
| <b>Fastener Length:</b>                               | 1.000 Inches Nominal  |
| <b>Head Style:</b>                                    | Round Extended Washer   |
| <b>Head Diameter:</b>                                 | 0.375 Inches Nominal  |
| <b>Head Height:</b>                                   | 0.094 Inches Nominal  |
| <b>Extended Washer Diameter:</b>                      | 0.437 Inches Nominal  |
| <b>Extended Washer Thickness:</b>                     | 0.027 Inches Nominal  |
| <b>Grip Diameter:</b>                                 | 0.189 Inches Nominal  |
| <b>Internal Drive Style:</b>                          | Cruciform Ribbed  |
| <b>End Item Identification:</b>                       | Support Of Pre-provisioning Items For Which Navicp Phil Acts As Poe (e-nsn Isil)                    |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches  |
| <b>Grip Length:</b>                                   | 0.438 Inches Nominal  |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Minimum Tensile Strength:</b>                      | 2000 Pounds Per Square Inch   |
| <b>Criticality Code Justification:</b>                | Agav  |
| <b>Part Name Assigned By Controlling Agency:</b>      | Screw, Washer Head, Close Tolerance, Long Thread, 95 Ksi Fsu  |
| <b>Material:</b>                                      | Steel Comp 4340 Overall   |
| <b>Material Document And Classification:</b>          | Ams6415 Assn Std 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416, Type 2, Class2 Fed Spec Single Treatment Response Overall                                 |
| <b>Thread Series Designator:</b>                      | Unjf  |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/120-225-3R14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.