

**Description**

Fastener Length: 1", Thread: 10-32, Thread Length: 27/64

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	1202253R14
Minimum Qty (MOQ):	50
NSN:	5305-01-524-1511
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

## P/N 120-225-3R14 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.429 Inches Nominal
<b>Fastener Length:</b>	1.000 Inches Nominal
<b>Head Style:</b>	Round Extended Washer
<b>Head Diameter:</b>	0.375 Inches Nominal
<b>Head Height:</b>	0.094 Inches Nominal
<b>Extended Washer Diameter:</b>	0.437 Inches Nominal
<b>Extended Washer Thickness:</b>	0.027 Inches Nominal
<b>Grip Diameter:</b>	0.189 Inches Nominal
<b>Internal Drive Style:</b>	Cruciform Ribbed
<b>End Item Identification:</b>	Support Of Pre-provisioning Items For Which Navicp Phil Acts As Poe (e-nsn Isil)
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.438 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	2000 Pounds Per Square Inch
<b>Criticality Code Justification:</b>	Agav
<b>Part Name Assigned By Controlling Agency:</b>	Screw, Washer Head, Close Tolerance, Long Thread, 95 Ksi Fsu
<b>Material:</b>	Steel Comp 4340 Overall
<b>Material Document And Classification:</b>	Ams6415 Assn Std 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Type 2, Class2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/120-225-3R14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.