

Description

Fastener Length: 3/8", Thread: 8-32, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	120225C08R06
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-612-6086
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N 120-225C08R06 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.398 Inches Nominal
Fastener Length:	0.406 Inches Nominal
Head Style:	Round Extended Washer
Head Diameter:	0.312 Inches Nominal
Head Height:	0.082 Inches Minimum And 0.092 Inches Maximum
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.023 Inches Minimum And 0.028 Inches Maximum
Grip Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Single Shear Strength:	95000 Pounds Per Square Inch
Internal Drive Style:	Cruciform Ribbed
End Item Identification:	Navy Aircraft
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.032 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	2170 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Part Name Assigned By Controlling Agency:	Screw,washer Head,close Tolerance,long Thread,95ksi Fsu
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	A286 law Ams5731,ams5732,ams5737 Or Ams5853 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Ams-qq-p-35 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/120-225C08R06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.