

Description

Fastener Length: 15/16", Thread: 10-32, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	120225C313
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-524-1549
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N 120-225C3-13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.430 Inches Nominal
Fastener Length:	0.938 Inches Nominal
Head Style:	Round Extended Washer
Head Diameter:	0.375 Inches Nominal
Head Height:	0.094 Inches Nominal
Extended Washer Diameter:	0.437 Inches Nominal
Extended Washer Thickness:	0.027 Inches Nominal
Grip Diameter:	0.189 Inches Nominal
Internal Drive Style:	Cruciform Ribbed
End Item Identification:	Support Of Pre-provisioning Items For Which Navicp Phil Acts As Poe (e-nsn Isil)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.375 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	2000 Pounds Per Square Inch
Criticality Code Justification:	Agav
Part Name Assigned By Controlling Agency:	Screw, Washer Head, Close Tolerance, Long Thread, 95 Ksi Fsu
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Overall Or Ams5732 Fed Spec 2nd Material Response Overall Or Ams5737 Assn Std 3rd Material Response Overall Or Ams5853 Assn Std 4th Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/120-225C3-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.