

**Description**

Fastener Length: 5/8", Thread: 8-32, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	120225V0809
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-513-4311
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N 120-225V08-09 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.438 Inches Nominal
<b>Fastener Length:</b>	0.579 Inches Minimum And 0.626 Inches Maximum
<b>Head Style:</b>	Round Extended Washer
<b>Head Diameter:</b>	0.312 Inches Nominal
<b>Head Height:</b>	0.082 Inches Minimum And 0.092 Inches Maximum
<b>Extended Washer Diameter:</b>	0.375 Inches Nominal
<b>Extended Washer Thickness:</b>	0.023 Inches Minimum And 0.028 Inches Maximum
<b>Grip Diameter:</b>	0.1625 Inches Minimum And 0.1635 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type Ii
<b>End Item Identification:</b>	V-22
<b>Nominal Thread Diameter:</b>	0.1640 Inches
<b>Grip Length:</b>	0.141 Inches Minimum And 0.171 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Criticality Code Justification:</b>	Agav
<b>Part Name Assigned By Controlling Agency:</b>	Screw,machine,aircraft
<b>Special Features:</b>	Finish - Aluminum Epoxy Per Nas4006; 160-180 Ksi FtU Per Ams 4928 Or Ams 4967
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/120-225V08-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.