

P/N 120-225V08-09

Military-Fasteners.com

#### Description

Fastener Length: 5/8", Thread: 8-32, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	120225V0809
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-513-4311
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N 120-225V08-09 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	0.579 Inches Minimum And 0.626 Inches Maximum
Head Style:	Round Extended Washer
Head Diameter:	0.312 Inches Nominal
Head Height:	0.082 Inches Minimum And 0.092 Inches Maximum
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.023 Inches Minimum And 0.028 Inches Maximum
Grip Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Internal Drive Style:	Cross Recess Type li
End Item Identification:	V-22
Nominal Thread Diameter:	0.1640 Inches
Grip Length:	0.141 Inches Minimum And 0.171 Inches Maximum
Thread Quantity Per Inch:	32
Criticality Code Justification:	Agav
Part Name Assigned By Controlling Agency:	Screw, machine, aircraft
Special Features:	Finish - Aluminum Epoxy Per Nas4006; 160-180 Ksi Ftu Per Ams 4928 Or Ams 4967
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjc

## **How to Order**

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/120-225V08-09</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.