

Description

Fastener Length: 3/8", Thread: 10-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	120259E3P2
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-520-9378
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 120-259E3P2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.260 Inches Nominal
Fastener Length:	0.528 Inches Nominal
Head Style:	Undercut Pan No. 2
Head Diameter:	0.547 Inches Nominal
Head Height:	0.127 Inches Nominal
Spline Major Diameter:	0.155 Inches Nominal
Grip Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Internal Drive Style:	Torx
End Item Identification:	Mv-22 (v-22 Lrip 1 E-nsn Isil
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.125 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	3180 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Screw, Shear, Pan Head, Close Tolerance, Short Thread, Six Lobe Recess, 95 Ksi Fsu
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Fed Spec 1st Material Response Overall Or Ams 5732 Fed Spec 2nd Material Response Overall Or Ams 5737 Fed Spec 3rd Material Response Overall Or Ams 5853 Fed Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ms-qq-p-416, Type 2, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/120-259E3P2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.