

## Description

Fastener Length: 3/4", Thread: 10-32, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	120259V3A6
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-520-9386
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N 120-259V3A6 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.260 Inches Nominal
<b>Fastener Length:</b>	0.778 Inches Nominal
<b>Head Style:</b>	Undercut Pan No. 2
<b>Head Diameter:</b>	0.547 Inches Nominal
<b>Head Height:</b>	0.127 Inches Nominal
<b>Spline Major Diameter:</b>	0.155 Inches Nominal
<b>Grip Diameter:</b>	0.189 Inches Nominal
<b>Internal Drive Style:</b>	Torx
<b>End Item Identification:</b>	Mv-22 (v-22 Lrip1)
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.375 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	3180 Pounds Per Square Inch
<b>Part Name Assigned By Controlling Agency:</b>	Screw, Shear, Pan Head, Close Tolerance, Short Thread, Six Lobe Recess, 95 Ksi Fsu
<b>Material:</b>	Titanium Alloy Uns R54520 Overall
<b>Material Document And Classification:</b>	Ams 4928 Fed Spec 1st Material Response Overall Or Ams 4967 Fed Spec 2nd Material Response Overall
<b>Surface Treatment:</b>	Paint Overall And Lubricant Overall
<b>Surface Treatment Document And Classification:</b>	Nas4006 Assn Std 1st Treatment Response Overall And Cetyl Alcohol Lubricant Per Mil-I-87132, Type 3, Grade B Mil Spec 2nd Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/120-259V3A6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.