

Description

Fastener Length: 1-27/64", Thread: 1/4-28, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	120259V4A15
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-519-1481
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 120-259V4A15 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.298 Inches Nominal
Fastener Length:	1.422 Inches Nominal
Head Style:	Undercut Pan No. 2
Head Diameter:	0.482 Inches Nominal
Head Height:	0.168 Inches Nominal
Spline Major Diameter:	0.221 Inches Nominal
Grip Diameter:	0.248 Inches Minimum And 0.249 Inches Maximum
Internal Drive Style:	Torx
End Item Identification:	Mv-22 (v-22 Lrip1)
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.938 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	5820 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Screw, Shear, Pan Head, Close Tolerance, Short Thread, Six Lobe Recess, 95 Ksi Fsu
Material:	Titanium Alloy Uns R54520 Overall
Material Document And Classification:	Ams 4928 Fed Spec 1st Material Response Overall Or Ams 4967 Fed Spec 2nd Material Response Overall
Surface Treatment:	Paint Overall And Lubricant Overall
Surface Treatment Document And Classification:	Nas4006 Assn Std 1st Treatment Response Overall And Cetyl Alcohol Lubricant Per Mil-I-87132, Type 3, Grade B Mil Spec 2nd Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/120-259V4A15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.