

Description

Fastener Length: 5/8", Thread: 1/4-28, Thread Length: 17/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	120264E410
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-519-1369
Schedule B:	7318.15.6080
ECCN:	9A991



\* See page 2 for technical characteristics

# P/N 120-264E4-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.519 Inches Nominal
Fastener Length:	0.625 Inches Nominal
Head Style:	Flat Countersunk
Spline Major Diameter:	0.220 Inches Minimum And 0.223 Inches Maximum
Internal Drive Style:	Torx
End Item Identification:	Mv-22 Aircraft (v-22 Lrip 1 E-nsn Isil)
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	5820 Pounds Per Square Inch
Criticality Code Justification:	Agav
Part Name Assigned By Controlling Agency:	Screw,100 Degree Flush Head,full Thread,6 Lobe Recess
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams5731 Assn Std Single Material Response Or Ams5732 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response Or Ams5835 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Ams2700method 1,type2 Assn Std Single Treatment Response Or Ams2700method 1,type8,class 1 Assn Std Single Treatment Response
Thread Series Designator:	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/120-264E4-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.