

**Description**

Fastener Length: 5/8", Thread: 1/4-28, Thread Length: 17/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	120264E410
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-519-1369
Schedule B:	7318.15.6080
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N 120-264E4-10 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.519 Inches Nominal
<b>Fastener Length:</b>	0.625 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Spline Major Diameter:</b>	0.220 Inches Minimum And 0.223 Inches Maximum
<b>Internal Drive Style:</b>	Torx
<b>End Item Identification:</b>	Mv-22 Aircraft (v-22 Lrip 1 E-nsn Isil)
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	5820 Pounds Per Square Inch
<b>Criticality Code Justification:</b>	Agav
<b>Part Name Assigned By Controlling Agency:</b>	Screw,100 Degree Flush Head,full Thread,6 Lobe Recess
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Or Ams5732 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response Or Ams5835 Assn Std Single Material Response
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Ams2700method 1,type2 Assn Std Single Treatment Response Or Ams2700method 1,type8,class 1 Assn Std Single Treatment Response
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/120-264E4-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.