

Description

Fastener Length: 7/16", Thread: 10-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	120265E33
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-520-9391
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 120-265E3-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.260 Inches Nominal
Fastener Length:	0.464 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.380 Inches Nominal
Spline Major Diameter:	0.155 Inches Nominal
Grip Diameter:	0.189 Inches Nominal
Internal Drive Style:	Torx
End Item Identification:	Mv-22 Aircraft (v-22 Lrip 1 E-nsn Isil)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.188 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	3180 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Part Name Assigned By Controlling Agency:	Screw, Shear, Flat 100 Deg Head, Close Tolerance, Short Thread, Six Lobe Recess, 95 Ksi Fsu
Special Features:	This Screw Is Intended For Applications Which Require The Six Lobe Recess; Has Undrilled Shank
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Fed Spec 1st Material Response Overall Or Ams5732 Fed Spec 2nd Material Response Overall Or Ams5737 Fed Spec 3rd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Ams-qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/120-265E3-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.