

Description

Fastener Length: 7/8", Thread: 10-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	120265E3P10
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-520-9395
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N 120-265E3P10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.260 Inches Nominal
Fastener Length:	0.901 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.380 Inches Nominal
Spline Major Diameter:	0.189 Inches Nominal
Grip Diameter:	0.163 Inches Nominal
Internal Drive Style:	Torx
End Item Identification:	Mv-22 Aircraft (v-22 Lrip 1 E-nsn Isil)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.625 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	3180 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Part Name Assigned By Controlling Agency:	Screw, Shear, Flat 100 Deg Head, Close Tolerance, Short Thread, Six Lobe Recess, 95 Ksi Fsu
Special Features:	This Screw Is Intended For Applications Which Require The Six Lobe Recess; Has Undrilled Shank
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Fed Spec 1st Material Response Overall Or Ams5732 Fed Spec 2nd Material Response Overall Or Ams5737 Fed Spec 3rd Material Response Overall Or Ams5853 Fed Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams-qq-p-416, Type 2, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/120-265E3P10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.