

**Description**

Fastener Length: 7/8", Thread: 10-32, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                               |
|-------------------------|-------------------------------|
| SKU / Model:            | 120265E3P10                   |
| Minimum Qty (MOQ):      | 5 EA                          |
| NSN:                    | 5305-01-520-9395              |
| Schedule B:             | 7318.15.6080                  |
| ECCN:                   | 9A991                         |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE  
AVAILABLE

## P/N 120-265E3P10 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.260 Inches Nominal   |
| <b>Fastener Length:</b>                               | 0.901 Inches Nominal   |
| <b>Head Style:</b>                                    | Flat Countersunk   |
| <b>Head Diameter:</b>                                 | 0.380 Inches Nominal   |
| <b>Spline Major Diameter:</b>                         | 0.189 Inches Nominal   |
| <b>Grip Diameter:</b>                                 | 0.163 Inches Nominal   |
| <b>Internal Drive Style:</b>                          | Torx   |
| <b>End Item Identification:</b>                       | Mv-22 Aircraft (v-22 Lrip 1 E-nsn Isil)  |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches   |
| <b>Grip Length:</b>                                   | 0.625 Inches Nominal   |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Minimum Tensile Strength:</b>                      | 3180 Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                             | 100.0 Degrees Nominal  |
| <b>Part Name Assigned By Controlling Agency:</b>      | Screw, Shear, Flat 100 Deg Head, Close Tolerance, Short Thread, Six Lobe Recess, 95 Ksi Fsu  |
| <b>Special Features:</b>                              | This Screw Is Intended For Applications Which Require The Six Lobe Recess; Has Undrilled Shank   |
| <b>Material:</b>                                      | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b>          | Ams5731 Fed Spec 1st Material Response Overall Or Ams5732 Fed Spec 2nd Material Response Overall Or Ams5737 Fed Spec 3rd Material Response Overall Or Ams5853 Fed Spec 4th Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b> | Ams-qq-p-416, Type 2, Class 2 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/120-265E3P10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.