

Description

Fastener Length: 1-15/64", Thread: 1/4-28, Head Width: 9/64", Thread Length: 45/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	12000046
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-149-1933
Schedule B:	7318.15.8085
ECCN:	9A991.
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 120000-4-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.567 Inches Minimum And 0.706 Inches Maximum
Fastener Length:	1.237 Inches Nominal
Head Style:	Oval Countersunk
Head Diameter:	0.430 Inches Minimum And 0.440 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.141 Inches Minimum And 0.143 Inches Maximum
Thread Quantity Per Inch:	28
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Furnished With One Spring,thread To Be Double Lead.
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/120000-4-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.