



★ FASTENERS

Military-Fasteners.com

P/N 1204-0306

Description

Fastener Length: 1/4", 1204-03 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	12040306
Minimum Qty (MOQ):	100
NSN:	5320-00-714-7493
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N 1204-0306 Specifications

Fastener Length:	0.183 Inches Minimum And 0.193 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.095 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.178 Inches Minimum And 0.186 Inches Maximum
Expansion Device:	Knob Stem-type K
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp 1012 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/1204-0306> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.