



Military-Fasteners.com

P/N 1204-0316

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	12040316
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-145-1977
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N 1204-0316 Specifications

Fastener Length:	0.500 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.094 Inches Minimum And 0.096 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.164 Inches Minimum And 0.179 Inches Maximum
Expansion Device:	Mandrel-type C
Grip Length:	0.376 Inches Minimum And 0.437 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 1012 Sleeve
Material Document And Classification:	S.a.e. 1012 Assn Std Single Material Response Sleeve
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/1204-0316> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.