

P/N 122147

Military-Fasteners.com

Description

Fastener Length: 3-25/64", Hole Diameter: 3/64", Thread: 11/16-16, Thread Length: 1-3/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	122147
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-067-6372
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N 122147 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	1.188 Inches Nominal
Fastener Length:	3.361 Inches Minimum And 3.391 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.656 Inches Nominal
Extended Washer Diameter:	1.500 Inches Nominal
Extended Washer Thickness:	0.129 Inches Nominal
Shoulder Diameter:	1.000 Inches Minimum First Shoulder And 1.002 Inches Maximum First Shoulder
Shoulder Length:	1.250 Inches Minimum First Shoulder And 1.255 Inches Maximum First Shoulder
Hole Diameter:	0.050 Inches Minimum And 0.060 Inches Maximum
Head Minor Diameter:	0.673 Inches Minimum And 0.688 Inches Maximum
Nominal Thread Diameter:	0.688 Inches
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	260000 Pounds Per Square Inch
Hardness Rating:	51.0 Rockwell C Minimum Overall And 54.0 Rockwell C Maximum Overall
Hole Configuration Style:	Spline
Shoulder Shape:	Round First Shoulder
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Mil-c-8837,ty 2,cl 2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Un

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/122147</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.