

## P/N 13100001-4-3

## **Description**

13100001-4-3 Clip-On Nut

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

SL213-3-1

SKU / Model: 1310000143

Minimum Qty (MOQ): 10

NSN: 5310-01-396-5259

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N 13100001-4-3 Specifications**

Thread Class:	2b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Overall Width:	0.458 Inches Maximum
Nut Style:	Floating
Distance From Base To Center Of Aperture:	0.380 Inches Minimum And 0.500 Inches Maximum
Panel Thickness:	0.160 Inches Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 1 Fed Spec Single Treatment Response Overall

## **How to Order**

Order this clip-on nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/clip\_on+nuts/13100001-4-3">https://military-fasteners.com/nuts/clip\_on+nuts/13100001-4-3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/clip\_on+nuts/13100001-4-3">https://military-fasteners.com/nuts/clip\_on+nuts/13100001-4-3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/clip\_on+nuts/13100001-4-3">https://military-fasteners.com/nuts/clip\_on+nuts/13100001-4-3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/clip\_on+nuts/13100001-4-3">https://military-fasteners.com/nuts/clip\_on+nuts/13100001-4-3</a> and selecting the quantity you want then