

## P/N 13100003

## **Description**

Thread Size: 3/16"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

 SKU / Model:
 13100003

 Minimum Qty (MOQ):
 40 EA

 NSN:
 5310-01-455-9859

 Schedule B:
 7318.16.0085

ECCN: EAR99



<sup>\*</sup> See page 2 for technical characteristics

# P/N 13100003 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Overall Width:	0.400 Inches Maximum
Nut Style:	Floating
Distance From Base To Center Of Aperture:	0.575 Inches Minimum And 0.605 Inches Maximum
Panel Thickness:	0.130 Inches Nominal
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Special Features:	0.023 In. Max Mat Thk
Material:	Steel Comp 1050 Clip Or Steel Comp 4130 Clip
Material:	Steel Comp 4130 Nut Or Steel Comp 4037 Nut
Material Document And Classification:	Ams 6350 Assn Std Single Material Response Nut Or Ams 6300 Assn Std Single Material Response Nut
Material Document And Classification:	Ams5085 Assn Std Single Material Response Clip Or Ams 6350 Assn Std Single Material Response Clip
Surface Treatment:	Cadmium Clip And Chromate Clip
Surface Treatment:	Cadmium Nut And Chromate Nut
Surface Treatment Document And Classification:	Qq-p-416, Ty 2, Cl 2 Fed Spec Single Treatment Response Clip
Surface Treatment Document And Classification:	Qq-p-416, Ty 2, Cl 2 Fed Spec Single Treatment Response Nut

### **How to Order**

Order this clipnut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/clip\_on+nuts/13100003">https://military-fasteners.com/nuts/clip\_on+nuts/13100003</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.