

Description

Length: 1-11/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | 1334 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 3120-00-097-1155 |
| Schedule B: | 7318.29.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 114850, Bearing / Bushing O / T Ball / Roller I / S |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 1334 Specifications

| | |
|--|--|
| Overall Length: | 1.3450 Inches Minimum And 1.3510 Inches Maximum |
| Body Outside Diameter: | 0.6510 Inches Minimum And 0.6610 Inches Maximum |
| Body Inside Diameter: | 0.5630 Inches Minimum And 0.5650 Inches Maximum |
| Left Flange Outside Diameter: | 0.7080 Inches Minimum And 0.7100 Inches Maximum |
| Right Flange Outside Diameter: | 0.6820 Inches Minimum And 0.6870 Inches Maximum |
| Left Flange Width: | 0.3125 Inches Nominal |
| Right Flange Width: | 0.1293 Inches Nominal |
| Lubricant Accommodation Style: | Grooved Circular |
| Corner Shape: | Square All Corners |
| Surface Finish: | 20.0 Microinches Outside Diameter Surface Of Left Flange |
| Surface Finish: | 63.0 Microinches Left End Surface Of Body |
| Surface Groove Location And Quantity: | 1 Internal |
| Material: | Nickel Alloy 400 Overall |
| Material Document And Classification: | Qq-n-281,class A Fed Spec Single Material Response Overall |
| Style Designator: | 18c Solid, External Flanges Both Ends |
| Style Designator: | Solid, External Flanges Both Ends |

How to Order

Order this unknown from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/1334> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.